

MPX Series

Compact, reliable and designed for intensive applications, these generators offer a good mix of performance and endurance.



* Standard equipment sockets, see Technical Data

Main applications:

- Light duty applications
- Leisure
- DIY



**READY TO USE.
TRANSPORTATION KIT ALREADY ASSEMBLED,
NO TOOLS REQUIRED**



**AUTOMATIC VOLTAGE REGULATION (AVR) - AS
STANDARD - FOR STABILIZING THE OUTPUT
VOLTAGE**



**OPTIONAL:
MANUAL TRANSFER SWITCH 40A
(FOR MANUAL CONTROL VERSIONS)**



**INCREASED AUTONOMY THROUGH THE BIG
INTEGRATED METAL FUEL TANK OF 25,5
LITERS (MPX4000 EXCLUDED)**



**CONTROL PANEL WITH SOCKETS AND 3
FUNCTIONS DIGITAL SCREEN AVAILABLE
(HOURMETER, VOLTMETER, FREQUENCY
METER)**



**QUICK START SLIDE-OUT INSTRUCTION GUIDE
LOCATED BELOW THE CONTROL PANEL**

GENERATING SET	MPX 4000	MPX 5000	MPX 8000
MAIN DATA	SINGLE PHASE	SINGLE PHASE	SINGLE PHASE
POWER RATING - SINGLE PHASE	kVA / kW_e	kVA / kW_e	kVA / kW_e
STAND-BY POWER - LTP	3,5 / 3,5	5,9 / 5,9	6,4 / 6,4
CONTINUOUS POWER - COP	3,2 / 3,2	5,5 / 5,5	6,0 / 6,0
VOLTAGE (Volt)	120 / 240	120 / 240	120 / 240
FREQUENCY (Hz)	60	60	60
POWER FACTOR (Cos φ)	1	1	1
ENGINE			
BRAND	MASONS OHV	MASONS OHV	MASONS OHV
FUEL	Petrol	Petrol	Petrol
CYLINDERS / DISPLACEMENT (cc)	1 inclined / 208	1 inclined / 420	1 inclined / 420
COOLING SYSTEM	Air	Air	Air
STARTING SYSTEM	Recoil	Recoil	Electric (+ Recoil)
SPEED (rpm)	3600	3600	3600
CONSUMPTION			
FUEL CONSUMPTION at 75% of load (L/h)	1,86	2,51	2,81
FUEL TANK CAPACITY (L)	18,5	25,5	25,5
RUNNING TIME at 75% of load (h)	9,95	10,16	9,07
OVERALL DIMENSIONS (WITH WHEEL KIT ASSEMBLED)			
LENGTH (mm)	600	727	727
WIDTH (mm)	439	515	515
HEIGHT (mm)	588	670	670
DRY WEIGHT (Kg)	53	79	94
STANDARD EQUIPMENT			
DIGITAL DISPLAY	V - Hz - h	V - Hz - h	V - Hz - h
TANK (Type)	Metal	Metal	Metal
ANALOG INSTRUMENTS	Fuel gauge	Fuel gauge	Fuel gauge
SOCKETS	1 x DPLX 120V NEMA 5-20R 1 x TL 120/240V NEMA L14-20	1 x DPLX 120V NEMA 5-20R 1 x TL 120/240V NEMA L14-30R	1 x DPLX 120V NEMA 5-20R 1 x TL 120/240V NEMA L14-30R
AVR - AUTOMATIC VOLTAGE REGULATOR	Standard	Standard	Standard
TRANSPORTATION KIT	Standard	Standard	Standard
PROTECTIONS			
OIL GUARD	Standard	Standard	Standard
THERMAL PROTECTION	Standard	Standard	Standard
ALTERNATOR PROTECTION (IP)	23	23	23
OPTIONALS			
MTS - MANUAL TRANSFER SWITCH	o	o	o

o = Accessory available



www.masonsgenerators.com

MASONS DISTRIBUTOR IN YOUR AREA IS:

PR MIDDLE EAST FZE

1206 JAFZA View 18, P.O. Box 262478 - Jebel Ali Free Zone - South 1, Dubai
Tel.: +971 4 8865275 - Fax: +971 4 8865276